

ELC WIND UP LIGHTING STANDS

ELC-500

- +↑ 3,20 m
10' 5.99"
- ⬇️ 100 Kg
220.46 lb
- ↓ 1,70 m
5' 6.92"
- ⚖️ 14 Kg
30.86 lb
- 🔧 450 kg
992.08 lb
- S **ASB SYSTEM**



ELC-502

- +↑ 4,20 m
13' 9.36"
- ⬇️ 100 Kg
220.46 lb
- ↓ 1,70 m
5' 6.92"
- ⚖️ 22 Kg
48.50 lb
- 🔧 450 Kg
992.08 lb
- S **ASB SYSTEM**

ELC TELESCOPIC LIFTING TOWERS (TOP-LOADER)



Automatic Safety Blocking System Guarantees maximum reliability and protection in the lifting and lowering process.



5 mm thick perforated metal strip, welded for extra safety. Special Epoxy anti-scratch paint finish (for outdoor use).



Auto-brake Winches (AL-KO) Comply with CE Machinery Directives.



Knobs to block the telescopic sections. Protective cover to prevent the cable from coming out of the self-lubricated pulleys.



Special non-rotating steel wire rope, with steel core, 3 times the strength required. Top section fitted with a reinforcing ferrule.



Rectangular legs with double ferrule to reinforce screw jack holes. Leveller screw jacks with double thread for a quick adjustment. Chrome foot plates with non-slip injection moulded rubber pads.



Base provided with spirit level (for correct vehicle adjustment) & fitted with 4 heavy-duty wheels (Ø100mm) with steel fastening plates secured by 4 bolts each.

ADAPTORS



+↑ Maximum Height

⬇️ Maximum Load

-↓ Folded Dimension

⚖️ Net Weight

🔧 Auto-brake Winch

S Safety

ELC-503

- +↑ 3,20 m
10' 5.99"
- ⚖ 125 Kg
275.58 lb
- ↓ 1,45 m
4' 9.09"
- ⚖ 24 Kg
52.91 lb
- 🔧 450 kg
992.08 lb
- S **ASB SYSTEM**



CERTIFIED
BGV C1

ELC-503G

- +↑ 5,00 m
16' 4.85"
- ⚖ 100 Kg
220.46 lb
- ↓ 1,99 m
6' 6.35"
- ⚖ 29 Kg
63.93 lb
- 🔧 500 Kg
1102.31 lb
- S **ASB SYSTEM**



ELC-504

- +↑ 4,22 m
13' 10.14"
- ⚖ 125 kg
275.58 lb
- ↓ 1,44 m
4' 8.69"
- ⚖ 42 Kg
92.59 lb
- 🔧 450 kg
992.08 lb
- S **ASB SYSTEM**



ELC-504G

- +↑ 5,20 m
17' 0.72"
- ⚖ 125 kg
275.58 lb
- ↓ 1,70 m
5' 6.92"
- ⚖ 46 Kg
101.41 lb
- 🔧 450 kg
992.08 lb
- S **ASB SYSTEM**



ELC-505

- +↑ 5,20 m
17' 0.72"
- ⚖ 200 kg
440.92 lb
- ↓ 1,75 m
5' 8.89"
- ⚖ 75 Kg
165.35 lb
- 🔧 900 Kg
1984.2 lb
- S **ASB SYSTEM**



ELC-506

- +↑ 5,20 m
17' 0.72"
- ⚖ 250 kg
551.15 lb
- ↓ 1,75 m
5' 8.89"
- ⚖ 95 Kg
209.44 lb
- 🔧 900 Kg PLUS
1984.2 lb
- S **ASB SYSTEM**

